



Government of Goa

**DIRECTORATE OF SKILL DEVELOPMENT & ENTREPRENEURSHIP
SATTARI GOVERNMENT INDUSTRIAL TRAINING INSTITUTE**

(An ISO:EOMS: 21001:2018 Certified Institute)

HONDA SATTARI – GOA 403530 Phone no. 0832 – 2370242

Website: www.itisattari.goa.gov.in

Email: sattari-iti.goa@nic.in

No:04/F-05/SGITI/STR/Electrician-Jr./2026-27/ 1320

Date: 02/04/2026

To,
Reputed supplier

Sub:- Inviting Limited Tender for supply of Training Materials for Electrician trade reg.
Sir,

Tenders are invited in sealed envelopes as per the specification and quantity mentioned in the attached "ANNEXURE-I".

Sr. No.	Description of Items	Qty.req.	Rate per Unit	Total	Remarks
1.	As per Enclosed Annexure-I				

The terms and conditions for the supply shall be as under:-

1. The material will have to be supplied/ installed within the period of 20 days from the dates of the supply order at Sattari Govt. Industrial Training Institute, Honda Sattari.
2. CST, Octroi, Sales Tax, GST and any other levy at the time of supply may be shown separately in the quotation; otherwise it will be presumed that the prices offered is inclusive of all taxes whatever may be.
3. The Tender will be evaluated for all items together.
4. The rate quoted shall be inclusive of packing and forwarding charges and freight paid for destination at Sattari Govt. ITI Honda, Sattari 403530.
5. The make, brand, model, etc. giving details of the items quoted for should be mention in the Tender or else the item shall be liable for rejection.
6. The material quoted should be of ISI standard or having ISO 9001/ISO9002 certification as the case may be whatever available.
7. The Tender shall be valid for 90 days from the date of the opening of the same.
8. The item will be inspected for acceptance in the presence of your representative and will be accepted if it confirms to the specification mentioned in the Annexure.
9. In case of rejection, for not confirming/matching as per supply order specification, the same will be sole responsibility of the supplier to make arrangement to collect the same at his own cost and risk immediately.
10. The transportation, installation and demonstration shall be at the cost of the supplier.
11. The tools and equipment s supplied as the case may be should carry warranty/ guarantee against defects.
12. This office reserves the right accept or reject any or all the tenders /Quotations without assigning any reason thereof.
13. This office reserves the right to place order for part/ full quantity mentioned in tenders for the purchase of the stores as the case may be.
14. In case of any dispute, the decision provided by an Arbitrator appointed by the Government will be final.
15. The Tender should be sent in sealed envelope superscripting "TENDER NUMBER & SUBJECT" so as to reach this office at **2:00PM on or before 13/04/2026** which will be opened on the same day at 03:00PM.

Yours faithfully,


(Niles P. Gawas)
Principal

Copy to:

1. Store copy


Annexure-I

S.No	Item Description	Detailed Specification	Qty	Unit	Unit Rate (₹)	Total Amount (₹)
1	Hack saw blade 24 TPI	High-carbon steel blade, precision-cut teeth, corrosion-resistant, durable cutting performance	50	Nos		
2	Aluminium lugs 2.5 sq mm pin type	High-conductivity aluminium, tin-plated, crimp-ready, corrosion-resistant	25	Nos		
3	Aluminium lugs 4.0 sq mm pin type	Tin-plated aluminium, easy crimping, excellent conductivity, corrosion-resistant	25	Nos		
4	PVC insulated copper wire 7/20 SWG	Flexible copper conductor, PVC insulation, flame-retardant, ISI/IEC compliant	2	Coils		
5	Resin core solder wire 60:40		1	Kg		
6	Aluminium lugs 1.5 sq.mm ring type	Tin-plated aluminium, high conductivity, corrosion-resistant, easy crimping	50	Nos		
7	Aluminium lugs 2.5 sq.mm ring type	Tin-plated aluminium, durable, corrosion-resistant, compatible with crimping tools	50	Nos		
8	Aluminium lugs 4.0 sq.mm ring type	High-quality aluminium, tin-plated, ensures low-resistance connection, corrosion-resistant	50	Nos		
9	Aluminium lugs 16 sq.mm ring type	Heavy-duty aluminium lug, tin-plated, corrosion-resistant, suitable for large cables	50	Nos		
10	Capacitor 2.5,4,10,15 µF	AC capacitor, metallized polypropylene, high dielectric strength, long life	5	Each		
11	Dry cell 1.5 V AA	Standard carbon-zinc dry cell, 1.5 V, long shelf life, reliable performance	10	Nos		
12	Dry cell 1.5 V AAA	Carbon-zinc AAA battery, 1.5 V, energy-efficient, long shelf life	10	Nos		
13	Dry cell 9V	9 V PP3 battery, high-density carbon-zinc or alkaline, consistent voltage output	10	Nos		
14	Indicating lamp 6A 250V flush type	LED/flame-retardant indicator lamp, flush mounting, 6 A, 250 V AC	10	Nos		
15	SP one way switch 6A 250V flush type	Single-pole, one-way switch, modular, fire-retardant thermoplastic body, 6 A, 250 V	20	Nos		
16	5 pin Socket 6A 250V flush type	5-pin socket, modular, heat-resistant, ISI standard, 6 A, 250 V AC	10	Nos		
17	Angle lamp holder camera type 6A 250V	Heat-resistant thermoplastic angle lamp holder, 6 A, 250 V, durable and shock-proof	50	Nos		
18	Batten lamp holder 6A 250V	Batten-type lamp holder, fire-retardant plastic, 6 A, 250 V AC, long life	50	Nos		
19	PVC Casing capping 3/4 inch	Rigid PVC casing/capping, corrosion-resistant, high mechanical strength	15	Nos		
20	PVC Casing capping 1 inch	1-inch PVC casing/capping, durable, fire-retardant, ISI standard	15	Nos		
21	SP two way switch flush type 6A/250 V	Single-pole, two-way switch, modular, fire-retardant, smooth operation, ISI standard	20	Nos		
22	Intermediate switch 6A 250 V	Intermediate modular switch, 6 A, 250 V, durable thermoplastic, smooth toggle	10	Nos		
23	Socket switch combination box 5 in 1 Box	Combination box with 5 modular outlets, fire-retardant PVC, easy mounting	10	Nos		
24	Modular MCB Single phase 10A 250V	Thermal-magnetic MCB, 10 A, 250 V, high breaking capacity, ISI/IEC standard	10	Nos		
25	MCB Single phase 15A 250V	15 A single-phase MCB, thermal-magnetic, durable, ISI/IEC standard	10	Nos		
26	MCB Single phase 20A 250V	20 A single-phase MCB, thermal-magnetic, high breaking capacity, compliant with standards	5	Nos		
27	MCB Single phase 6A 250V	6 A MCB, single-phase, compact design, high reliability, ISI standard	10	Nos		
28	MCB Single phase 10A 250V	10 A MCB, thermal-magnetic, high quality, modular-compatible	5	Nos		
29	PVC surface box 2md	PVC surface box, 2-module, fire-retardant, impact-resistant, ISI standard	30	Nos		
30	PVC surface box 3md	PVC 3-module surface box, durable, corrosion-resistant, easy mounting	10	Nos		
31	PVC surface box 4md	4-module surface box, high-impact PVC, fire-retardant, ISI standard	10	Nos		



S.No	Item Description	Detailed Specification	Qty	Unit	Unit Rate (₹)	Total Amount (₹)
32	PVC surface box 6md	6-module surface box, durable, corrosion-resistant, modular compatible	10	Nos		
33	PVC surface box 8md rectangular	Rectangular 8-module surface box, fire-retardant PVC, high durability	10	Nos		
34	PVC surface box 8md square	Square 8-module surface box, PVC, corrosion-resistant, ISI standard	10	Nos		
35	PVC surface box 12md	12-module surface box, high-quality PVC, impact-resistant, fire-retardant	3	Nos		
36	PVC surface box 16md	16-module surface box, modular, durable, fire-retardant, ISI standard	3	Nos		
37	PVC surface box 18md	18-module surface box, modular, durable, fire-retardant, ISI standard	3	Nos		
38	Switch board plate 18 module	18-module switch board plate, durable thermoplastic, fire-retardant, modular	3	Nos		
39	Switch board plate 1 module	1-module switch board plate, fire-retardant plastic, smooth finish, durable	30	Nos		
40	Switch board plate 2md	2-module plate, thermoplastic, fire-retardant, modular-compatible	30	Nos		
41	Switch board plate 3md	3-module switch board plate, durable thermoplastic, smooth finish	20	Nos		
42	Switch board plate 4md	4-module plate, fire-retardant, high-quality thermoplastic, ISI standard	20	Nos		
43	Switch board plate 6md	6-module switch board plate, fire-retardant, durable, modular-compatible	20	Nos		
44	Switch board plate 8md square	8-module square switch board plate, fire-retardant, corrosion-resistant, durable	10	Nos		
45	Switch board plate 8md rectangular	Rectangular 8-module switch board plate, durable, fire-retardant thermoplastic, ISI standard	10	Nos		
46	Switch board plate 12md	12-module switch board plate, fire-retardant, durable, modular-compatible	6	Nos		
47	Switch board plate 16md	16-module switch board plate, thermoplastic, fire-retardant, corrosion-resistant	3	Nos		
48	Switch board plate 18md	18-module switch board plate, high-quality, fire-retardant, durable, modular-compatible	3	Nos		
49	SP one way switch 10A modular type	Single-pole, one-way modular switch, thermoplastic, 10 A, 250 V, fire-retardant	30	Nos		
50	SP two way switch 10A modular type	Single-pole two-way modular switch, durable, smooth toggle, 10 A, 250 V	30	Nos		
51	Three pin socket 10A modular	Modular 3-pin socket, heat-resistant, fire-retardant plastic, 10 A, 250 V	30	Nos		
52	Double pole modular switch 32A 250V	Double-pole modular switch, 32 A, 250 V, high mechanical strength, fire-retardant	10	Nos		
53	MCB modular type 15A 250V	15 A modular MCB, thermal-magnetic, high breaking capacity, ISI/IEC standard	10	Nos		
54	SP one way switch 20A modular type	Single-pole one-way modular switch, 20 A, 250 V, durable thermoplastic body	10	Nos		
55	Three pin socket 20A modular	20 A modular socket, heat-resistant, fire-retardant, 250 V AC, ISI standard	20	Nos		
56	Ding dong bell	AC/DC electronic bell, durable plastic housing, low power consumption, long	5	Nos		
57	Bell push switch 6A modular	Modular bell push switch, 6 A, 250 V, fire-retardant, smooth operation	50	Nos		
58	Insulation tape Red/Yellow/Blue/Black	PVC insulation tape, 10 mm width, flame-retardant, durable, flexible	10	Each		
59	Connector strip 6A	PVC connector strip, 6 A, fire-retardant, durable, safe wiring connection	10	Nos		
60	Hookup wire single stranded	Single-stranded copper wire, PVC insulated, flexible, ISI standard	2	Coils		
61	Ceiling rose 6A/250 V	Durable thermoplastic ceiling rose, 6 A, 250 V, fire-retardant, smooth finish	20	Nos		
62	Pendant holder 6A/250V		20	Nos		
63	Showcase light fitting	LED showcase light, 20–30 W, energy-efficient, corrosion-resistant, high-lumen output	5	Nos		
64	Iron Thermostat switch	Thermostat switch, bimetallic, precise temperature control, durable metallic body	5	Nos		

S.No	Item Description	Detailed Specification	Qty	Unit	Unit Rate (₹)	Total Amount (₹)
65	Geyser Thermostat switch	Thermostat switch for water heaters, high-accuracy, heat-resistant, long life	2	Nos		
66	Mixture Carbon brush	Carbon brushes, high conductivity, low wear, suitable for electric mixers	5	Pairs		
67	Tripping switch mixture	Trip switch, overcurrent protection, durable thermoplastic, high reliability	2	Nos		
68	LED light fixture concealed 15 W tri-colour	15 W LED fixture, concealed mounting, tri-colour selectable, energy-efficient	10	Nos		
69	LED light fixture surface 15 W colour	Surface-mounted LED fixture, 15 W, energy-efficient, durable, high-lumen output	10	Nos		
70	Banana connector male female 16A		50	Nos		
71	Banana connector male female 16A		50	Nos		
72	PVC insulated copper wire 1 sq mm Red/Black/Green	High-conductivity copper, flexible PVC insulation, colour-coded for phase identification, fire-retardant ISI standard	2	Each		
73	PVC insulated copper wire 1.5 sq mm R/Y/B/Black	Premium 1.5 sq mm copper conductor with multi-colour PVC insulation, flame-retardant, long-lasting, ISI standard	6	Nos		
74	PVC insulated copper wire 2.5sq mm	Premium 2.5 sq mm copper conductor with multi-colour PVC insulation, flame-retardant, long-lasting, ISI standard	2	Nos		
75	PVC insulated copper wire 4sq mm	Premium 4 sq mm copper conductor with multi-colour PVC insulation, flame-retardant, long-lasting, ISI standard	1	Nos		
76	M.S drill bit 3,4,5 mm	High-speed steel drill bits, 3-5 mm, durable, precise cutting, corrosion-resistant	5	Each		
77	LED lamps 3,7,9 W 250V	LED lamps, 3/7/9 W, 250 V AC, energy-efficient, long-life, high-lumen output	2	Each		
78	Inverter lamp 9 W	9 W LED inverter-compatible lamp, high efficiency, stable operation on DC supply	2	Nos		
79	PVC 3 core cable 1.5 sq mm	Three-core copper conductor, flexible PVC insulation, colour-coded, flame-retardant, ISI/IEC compliant	1	coil		
80	Three pin top 6 A	3-pin plug, 6 A, durable thermoplastic, heat-resistant, ISI standard	6	Nos		
81	Three pin top 16 A	3-pin plug, 16 A, modular design, fire-retardant, durable, ISI compliant	6	Nos		
82	Two pin top 6 A	2-pin plug, 6 A, thermoplastic body, fire-retardant, durable	3	Nos		
83	Din rail	Galvanized steel DIN rail, 35 mm standard, corrosion-resistant, sturdy mounting for MCBs/MCBs	2	Meters		
					<u>Sub total Amount</u>	
					<u>GST</u>	
					<u>Grand Total Amount</u>	


 (Nilesh P. Gawas)
 Principal
 Sattari Govt. ITI